

# Christie HS Series

## D16WU-HS / D16HD-HS

Enterprise venues and boardrooms  
Entertainment venues  
Fixed installation  
Houses of worship

Hotels  
Live events and conferences  
Rental and staging  
Trade shows and exhibitions



## Power is freedom

Enjoy the freedom of unrestricted power. Hitting 16,000 lumens, the Christie® D16WU-HS and D16HD-HS are the lightest and brightest 1DLP® laser projectors to operate at full-brightness on a single 15A, 110V circuit. There's no need for high-power runs. Simply plug it into a standard outlet and start the show!

Visuals are stunning thanks to the enhanced color accuracy of Christie's patented BoldColor Technology and HD or WUXGA resolution. The long-lasting and reliable laser light source and affordability of 1DLP technology means these projectors are a cost-effective option for high-use applications. With built-in Christie Twist™, users have the tools needed to quickly and easily set up and align irregular screens and multi-projector displays.

**CHRISTIE®**

		Christie D16WU-HS	Christie D16HD-HS
Image	brightness (lumens)	• 17,400 ISO • 15,500 ANSI	• 15,750 ISO • 14,000 ANSI
	color wheel	• 4 segment (RGBY) - 2X or 3X speed	
	contrast (nominal)	• Full on/off (Christie RealBlack enabled): 2,000,000:1 • Dynamic contrast: 5000:1 • Full on/off (Christie RealBlack disabled): 1200:1 • ANSI 250:1	
Display technology	type	• 1 x 0.96" DMD	
	native resolution	• 1920 x 1200 (2,304,000 pixels) 16:10	• 1920 x 1080 (2,073,600 pixels) 16:9
Illumination	type	• Laser phosphor with Christie BoldColor Technology	
	typical lifetime	• 20,000 hrs to 50%	
Signal inputs	standard	• HDMI x 2 (one on rear panel, one on bottom of projector, independently selectable) • 3GSDI x 1 (BNC) • DVI-D x 1 (digital only) • HD15 x 1 • USB x 1 (Type A) • Image Viewer or Wi-Fi® dongle (optional) • HDBaseT x 1	
	signals	• HDTV formats VGA through to WUXGA (1920 x 1200) • Horizontal and vertical scaling while maintaining aspect ratio, all inputs	
	3D	• HDMI 1.4, HDBaseT - frame packed, top/bottom, side-by-side (up to 120Hz output) • 3D sync in (BNC) - for genlocking projectors • 3D Sync Out (BNC) - for genlocking projectors or controlling emitters	
	pixel clock	• 162MHz	
	scan rates	• Horizontal: 15kHz to 91kHz • Vertical: 24Hz to 85Hz	
	Signal outputs	monitor out (loop-through)	• 3GSDI x 1 (BNC) • HDMI x 1 (HDMI out)
Control and networking		• RS-232 in • Control via HDBaseT • Ethernet (10/100) RJ45 • Built-in backlit keypad • Wired remote control (3.5mm stereo) • Loop out available for daisy chaining • 12VDC trigger at 200mA (ID:2.5mm)	
Lenses	mount type	• Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses)	
	lens options	• 0.84-1.02:1 zoom lens (no zoom/focus memory) • 1.02-1.36:1 zoom lens (no zoom/focus memory) • 1.2-1.5:1 zoom lens (full ILS) • 1.5-2.0:1 zoom lens (full ILS) • 2.0-4.0:1 zoom lens (full ILS) • 4.0-7.0:1 zoom lens (full ILS)	
	offsets for full ILS lenses	• ±120% Vertical • ±50% Horizontal	• ±133% Vertical • ±50% Horizontal
	offsets for 0.84-1.02:1	• +37/-60% Vertical • +15/-44% Horizontal	• +110/-86% Vertical • +34/-39% Horizontal
	offsets for 1.02-1.36:1	• +51/-53% Vertical • +11/-50% Horizontal	• +125/-98% Vertical • +42/-47% Horizontal
Accessories	standard	• IR remote w/wired remote jack (wire not included) • AC line cord for projector head • User manual	
	optional	• Christie One Rigging Frame • Lens adapter for E Series lenses • 1DWUSB-BGN (wireless dongle for video and control) • Christie HS Series fog filter refills (1 set) • Christie HS Series fog filter covers and filters (order once per projector then only filter refills) • Christie One Mount Plus • One Mount Extender Rod • Replacement remote control • One Mount Rigging Kit (used with One Mount, One Mount Plus and/or One Mount Extender Rod)	
Power requirements	operating voltage	• Normal mode: 110-240 VAC @ 50/60Hz	
	power consumption	• Normal mode: 1250W ±15% (220 VAC), 1300W ±15% (110 VAC) • ECO1 mode: 1020W ±15% (220 VAC), 1050W ±15% (110 VAC) • ECO2 mode: 700W ±15% (220 VAC), 700W ±15% (110 VAC)	
	operating current	• Normal mode: 6.0A ±15% (220 VAC), 11.9A ±15% (110 VAC) • ECO1 mode: 4.7A ±15% (220 VAC), 9.6A ±15% (110 VAC) • ECO2 mode: 6.5A ±15% (220 VAC), 3.2A ±15% (110 VAC)	
	dissipation	• Normal mode: 4450 BTU/hr • ECO1 mode: 3600 BTU/hr • ECO2 mode: 2450 BTU/hr	
Audible noise		• Typical: 45dBA • Eco mode: 39dBA	
Physical	size	• (L xWxH) 26.65 x 23.46 x 7.99" (677 x 596 x 203mm) w/o feet	
	shipping size	• (L xWxH) 36.34 x 33.19 x 20.2" (923 x 843 x 513mm)	
	weight (w/o lens)	• 93.7lbs (42.5kg)	
	shipping weight	• 119lbs (54kg)	
Operating environment	temperature	• 32-104°F (0-40°C)	
	humidity	• 0-85% non-condensing	
Regulatory		• Contact Christie for the timing of certifications: UL/CSA/IEC 60950-1, FCC Class A, CE, FDA, CCC, KC, PSE, CU, SABS, BIS, VCCI, RCM, Ukr, TER, SASO • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • RoHS, REACH, WEEE	
Warranty		• Three years parts and labor on the projector • Three years or 15,000 hours parts and labor on the illumination system <sup>1</sup> • Contact an authorized Christie representative for full details of our limited warranty	

<sup>1</sup>Please reference Christie Standard Limited Warranty document for details.

#### Corporate offices

Christie Digital Systems USA, Inc.  
Cypress  
ph: 714 236 8610  
Christie Digital Systems Canada Inc.  
Kitchener  
ph: 519 744 8005

#### Worldwide offices

Australia  
ph: +61 (0) 7 3624 4888  
Brazil  
ph: +55 (11) 2548 4753  
China (Beijing)  
ph: +86 10 6561 0240  
China (Shanghai)  
ph: +86 21 6030 0500  
Columbia  
ph: +57 (318) 447 3179  
Eastern Europe  
ph: +36 (0) 1 47 48 138

France  
ph: +33 (0) 1 41 21 44 04  
Germany (Cologne)  
ph: +49 221 99 512-0  
Germany (Moechengladbach)  
ph: +49 2161 566200  
India  
ph: +91 (080) 6708 9999  
Japan  
ph: +81 3 3599 7481  
Mexico  
ph: +52 55 4744 1790

Republic of South Africa  
ph: +27 11 251 0000  
Singapore  
ph: +65 6877 8737  
South Korea  
ph: +82 2 702 1601  
Spain  
ph: +34 91 633 9990  
United Arab Emirates  
ph: +971 (0) 4 503 6800  
United Kingdom  
ph: +44 (0) 118 977 8000

United States (Arizona)  
ph: 602 943 5700  
United States (New York)  
ph: 646 779 2014

#### Independent sales consultant offices

Italy  
ph: +39 (0) 2 9902 1161  
Russia  
ph: +7 (495) 930 8961



For the most current specification information, please visit [www.christiedigital.com](http://www.christiedigital.com)